



0.6

LED 5W | 220-240VAC | 50-60Hz
COB 3-step | incl. power supply
stainless steel | glass
aluminium powder coated

0.38kg IP67 0.3m 38°

41 100

3000K | >80 CRI | 150lm

CODE

751163I4

0.9

LED 8W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
stainless steel | glass
aluminium powder coated

0.70kg IP67 0.3m 38°

78 135

3000K | >80 CRI | 480lm

CODE

751264I4

1.2

LED 12W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
stainless steel | glass
aluminium powder coated

1.01kg IP67 0.3m 38°

110 120

3000K | >80 CRI | 750lm

CODE

751364I4

1.6

LED 15W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
stainless steel | glass
aluminium powder coated

1.01kg IP67 0.3m 38°

150 185

3000K | >80 CRI | 950lm

CODE

751464I4

OPTIONAL

CODE

recessed housing 90012201

OPTIONAL

CODE

recessed housing 90012202

OPTIONAL

CODE

recessed housing 90012203

OPTIONAL

CODE

recessed housing 90012204