## TRAIN NARROW

## EXTERIOR WALL SURFACE







1.0

LED 6W | 220-240VAC | 50-60Hz COB 3-step | incl. power supply aluminium powder coated 2.0

© 2xLED 3W | 220-240VAC | 50-60Hz COB 3-step | incl. power supply aluminium powder coated

D → A 0.24kg ⊕ IP65 §+0,3→D 6

 $\boxed{\hspace{-0.5cm}\bigcirc\hspace{-0.5cm}} \hspace{0.5cm} \boxed{\hspace{-0.5cm}\bigcirc\hspace{-0.5cm}} \hspace{0.5cm} 0.35kg \hspace{0.5cm} \textcircled{\blacksquare} \hspace{0.5cm} \text{IP65} \hspace{0.5cm} \boxed{\hspace{-0.5cm}\bigcirc\hspace{-0.5cm}} ^{\hspace{0.5cm} \leftarrow\hspace{-0.5cm}} \hspace{0.5cm} 0,3\hspace{0.5cm} \nearrow \hspace{-0.5cm} \bigcirc \hspace{0.5cm} \bigcirc$ 

3000K | >80 CRI | 420lm

3000K | >80 CRI | 2x250lm narrow up/narrow down

CODE 719143D4

CODE 719243D4

3000K | >80 CRI | 2x250lm narrow up/flood down

CODE

719253D4

