




SQUBE on track

CEILING SURFACE



2.0 LED

LED 12W | 220-240VAC | 50-60Hz
 COB 3-step | incl. PS | phase-cut dim
 aluminium powder coated
 incl. 3-phase track adapter

0.40kg IP20 $\pm 0.3^\circ$ $\Delta 24^\circ$
 $\angle 90^\circ \curvearrowright 355^\circ$


CODE
144364W
144364B

Light Colour Selection

	LUMEN	CRI	CODE
2700K	780	>80	2
3000K	810	>80	4
1800-3000K	850	>80	9

OPTIONAL

	CODE
dimmer	
for switch	90019017
for din rail	90019018
more specs on page 576	
more track accessories on page 588	



3.0 LED

LED 20W | 220-240VAC | 50-60Hz
 COB 3-step | incl. PS | phase-cut dim
 aluminium powder coated
 incl. 3-phase track adapter

0.75kg IP20 $\pm 0.3^\circ$ $\Delta 31^\circ$
 $\angle 90^\circ \curvearrowright 355^\circ$

CODE
144564W
144564B

Light Colour Selection

	LUMEN	CRI	CODE
2700K	1380	>80	2
3000K	1520	>80	4
1800-3000K	1500	>80	9
2700K	1250	>90	3
3000K	1360	>90	5

OPTIONAL

	CODE
dimmer	
for switch	90019017
for din rail	90019018
more specs on page 576	
more track accessories on page 588	