




# RINI SNEAK

CEILING RECESSED



## 1.0 LED

LED 7/10W | 350-500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.18 kg <math>\triangleleft</math> IP44 <math>\approx</math> 0,3-1° <math>\odot</math> <math>\triangleleft</math> 38°

76 <math>\approx</math> 46 <math>\approx</math> 4-30

CODE

	154261W_
	154261B_

### Light Colour Selection

	LUMEN	CRI	CODE
2700K	420-590	>90	3
3000K	470-640	>90	5
1800-2850K	320-440	>95	9

## ALWAYS USE

power supply

CODE

350mA   10W	90213402
500mA   10W	90214403
500mA   15W dim	90224501

more power supplies on page 538

## 1.0 MR16

QR-CBC51 max. 35W | GU5.3  
12V | excl. power supply  
aluminium powder coated

0.12 kg <math>\triangleleft</math> IP44 <math>\approx</math> 0,9-1° <math>\odot</math>

76 <math>\approx</math> 55 <math>\approx</math> 4-30

CODE

	154210W0
	154210B0

## ALWAYS USE

power supply

CODE

12V   10W dim	90221401
12V   25W dim	90221701
12V   70W dim	90221904

more specs on page 540

## 1.0 PAR16

PAR16 max. 35W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.16 kg <math>\square</math> IP44 <math>\approx</math> 0,9-1° <math>\odot</math>

76 <math>\approx</math> 80 <math>\approx</math> 4-30

CODE

	154220W0
	154220B0

## OPTIONAL

PAR16 LED GU10 7W  
phase-cut dim

CODE

2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 541

