




PLUXO

CEILING SURFACE



1.0 LED111

LED 12W | 220-240VAC | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated


0.93kg IP20 0.3-1 P A 38°

45°/45° 45°/45°

CODE		
	143168W	...
	143168S	...
	143168B	...

Light Colour Selection

	LUMEN	CRI	CODE
2700K	680	>90	3
3000K	720	>90	5
1800-2850K	830	>80	9



2.0 LED111

2xLED 12W | 220-240VAC | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated


1.86kg IP20 0.3-1 P A 38°

45°/45° 45°/45°

CODE		
	143268W	...
	143268S	...
	143268B	...

Light Colour Selection

	LUMEN	CRI	CODE
2700K	2x680	>90	3
3000K	2x720	>90	5
1800-2850K	2x830	>80	9



3.0 LED111

3xLED 12W | 220-240VAC | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated


2.79kg IP20 0.3-1 P A 38°

45°/45° 45°/45°

CODE		
	143368W	...
	143368S	...
	143368B	...

Light Colour Selection

	LUMEN	CRI	CODE
2700K	3x680	>90	3
3000K	3x720	>90	5
1800-2850K	3x830	>80	9



4.0 LED111

4xLED 12W | 220-240VAC | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated

3.72kg IP20 0.3-1 P A 38°

45°/45° 45°/45°

CODE		
	143468W	...
	143468S	...
	143468B	...

Light Colour Selection

	LUMEN	CRI	CODE
2700K	4x680	>90	3
3000K	4x720	>90	5
1800-2850K	4x830	>80	9