




WETRO

CEILING SUSPENDED




1.0

LED 11W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
artisanal hand-blown glass

0.56 kg IP20 $\approx 0,3 \cdot D$

1800-2850K | >90 CRI | 400lm

| CODE | |
|------|----------|
| | 236189P9 |
| | 236189B9 |




2.0

LED 11W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
artisanal hand-blown glass

0.97 kg IP20 $\approx 0,3 \cdot D$

1800-2850K | >90 CRI | 400lm

| CODE | |
|------|----------|
| | 236289P9 |
| | 236289B9 |



3.0

LED 11W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
artisanal hand-blown glass

1.69 kg IP20 $\approx 0,3 \cdot D$

1800-2850K | >90 CRI | 400lm

| CODE | |
|------|----------|
| | 236389P9 |
| | 236389B9 |



As awarded by The Chicago Athenaeum:
Museum of Architecture and Design

ALWAYS USE

single ceiling base

| CODE | |
|------|----------|
| | 90052022 |
| | 90052021 |

multi- and other suspension options
on page 590

ALWAYS USE

single ceiling base

| CODE | |
|------|----------|
| | 90052022 |
| | 90052021 |

multi- and other suspension options
on page 590

ALWAYS USE

single ceiling base

| CODE | |
|------|----------|
| | 90052022 |
| | 90052021 |

multi- and other suspension options
on page 590

