





CHART

**EXTERIOR
FLOOR RECESSED**



0.6

LED 5W | 220-240VAC | 50-60Hz
COB 3-step | incl. power supply
stainless steel | glass
aluminium powder coated

0.39kg IP67 0.3-1D 38°

45 118

3000K | >80 CRI | 150lm

CODE

752163I4

0.9

LED 8W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
stainless steel | glass
aluminium powder coated

0.70kg IP67 0.3-1D

38°

78 135

3000K | >80 CRI | 480lm

CODE

752264I4

1.2

LED 12W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
stainless steel | glass
aluminium powder coated

1.05kg IP67 0.3-1D

38°

110 175

3000K | >80 CRI | 750lm

CODE

752364I4

1.6

LED 15W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
stainless steel | glass
aluminium powder coated

1.05kg IP67 0.3-1D

38°

150 185

3000K | >80 CRI | 950lm

CODE

752464I4

OPTIONAL

CODE

recessed housing 90012201

OPTIONAL

CODE

recessed housing 90012202

OPTIONAL


CODE

recessed housing 90012203

OPTIONAL

CODE

recessed housing 90012204



back