




**ROB**  
CEILING SURFACE



**1.6**

LED 12W | 220-240VAC | 50-60Hz  
PCB 3-step | phase-cut dim  
aluminium powder coated  
opal PMMA cover

0.70kg IP44

2700K | >80 CRI | 860lm

CODE  
701184W2

3000K | >80 CRI | 950lm

CODE  
701184W4  
701184S4

**OPTIONAL**

dimmer

CODE  
for switch 90019017  
for din rail 90019018

more specs on page 576

**2.6**

LED 18W | 220-240VAC | 50-60Hz  
PCB 3-step | phase-cut dim  
aluminium powder coated  
opal PMMA cover

1.20kg IP44

2700K | >80 CRI | 1250lm

CODE  
701284W2

3000K | >80 CRI | 1380lm

CODE  
701284W4  
701284S4

**OPTIONAL**

dimmer

CODE  
for switch 90019017  
for din rail 90019018

more specs on page 576

**3.5**

LED 32W | 220-240VAC | 50-60Hz  
PCB 3-step | phase-cut dim  
aluminium powder coated  
opal PMMA cover

1.90kg IP44

2700K | >80 CRI | 1820lm

CODE  
701384W2

3000K | >80 CRI | 1950lm

CODE  
701384W4  
701384S4

**OPTIONAL**

dimmer

CODE  
for switch 90019017  
for din rail 90019018

more specs on page 576