





PYRAMID

CEILING RECESSED



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.28kg IP20 3-0.3-1 36°

102x102 35°/35° 355° 90 4-30

1.0 PAR16

PAR16 max.35W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.26kg IP20 3-0.9-1

102x102 35°/35° 355° 115 4-30

2.0 LED

2xLED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.50kg IP20 3-0.3-1 36°

102x172 35°/35° 355° 90 4-30

2.0 PAR16

2xPAR16 max.35W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.46kg IP20 3-0.9-1

102x172 35°/35° 355° 115 4-30

CODE
113161W

CODE
113120W0

CODE
113261W

CODE
113220W0

Light Colour Selection

	LUMEN	CRI	CODE
2700K	420-590	>90	3
3000K	470-640	>90	5
1800-2850K	320-440	>95	9

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

CODE
2700K 901228W2
3000K 901228W4
1800-2850K 901229S9

ALWAYS USE

power supply	CODE
350mA 10W	90223401
500mA 10W	90214404
500mA 15W dim	90224501

more power supplies on page 574

Light Colour Selection

	LUMEN	CRI	CODE
2700K	2x420-590	>90	3
3000K	2x470-640	>90	5
1800-2850K	2x320-440	>95	9

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

CODE
2700K 901228W2
3000K 901228W4
1800-2850K 901229S9

ALWAYS USE

power supply	CODE
350mA 10W	90223401
500mA 10W	90214404
500mA 15W dim	90224501

more power supplies on page 574