



1.0 LED

LED AC MOD 8W | 220-240V
COB 3-step | incl. PS | phase cut dim
aluminum powdercoated

0.20kg IP20 3-0.3-D 36°

80 28°/28° 355° 70 4-18

wire springs

	CODE
	160168W_
	160168B_

blade springs

	CODE
	160168W_C
	160168B_C

Light Colour Selection

	LUMEN	CRI	CODE
2700K	480	>90	3
3000K	500	>90	5

fits into Kaiser ThermoX® 9320-21

1.0 MR16

QR-CBC51 max.35W | GU5.3
12V | excl. power supply
aluminium powder coated
matt chrome

0.14kg IP20 3-0.9-D

80 35°/35° 355° 70 4-18

wire springs

	CODE
	160110W0
	160110B0

blade springs

	CODE
	160110W0C
	160110B0C

ALWAYS USE

power supply	CODE
12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904

more specs on page 576
fits into Kaiser ThermoX® 9320-21

1.0 PAR16

PAR16 max.35W | GU10
100-240VAC | 50-60Hz
aluminium powder coated
matt chrome

0.18kg IP20 3-0.9-D

80 35°/35° 355° 70 4-18

wire springs

	CODE
	160120W0
	160120B0

blade springs

	CODE
	160120W0C
	160120B0C

OPTIONAL

PAR16 LED GU10 7W phase-cut dim	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 577
fits into Kaiser ThermoX® 9320-21