






DEEP ADJUST

CEILING RECESSED



1.0 LED111

LED 12W | 220-240VAC | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated

0.65kg IP20 3-0,3-D 38°

177 35°/35° 355° 100 4-30

	CODE
White	112568W
Black	112568B

Light Colour Selection

	LUMEN CRI	CODE
2700K	680 >90	3
3000K	720 >90	5
1800-2850K	830 >80	9

1.0 LED111 HO

LED 15W | 220-240VAC | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated

0.65kg IP20 3-0,3-D 30°

177 35°/35° 355° 100 4-30

	CODE
White	112578W
Black	112578B

Light Colour Selection

	LUMEN CRI	CODE
2700K	1050 >80	2
3000K	1200 >80	4

1.0 QR111

QR111 max.75W | G53
12V | excl. power supply
aluminium powder coated

0.41kg IP20 3-0,9-D

177 35°/35° 355° 100 4-30

	CODE
White	112530W
Black	112530B

ALWAYS USE

power supply

	CODE
12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904

more specs on page 576