

### 1.0

LED 8W | 220-240VAC | 50-60Hz  
COB 3-step | incl. PS | phase-cut dim  
aluminium powder coated


1.01kg | IP54 |  $\approx 0.3$  |  $\odot$

$\angle$  140°/140°

3000K | >80 CRI | 480lm

CODE

720174D4



### 2.0

2xLED 8W | 220-240VAC | 50-60Hz  
COB 3-step | incl. PS | phase-cut dim  
aluminium powder coated

1.10kg | IP54 |  $\approx 0.3$  |  $\odot$

$\angle$  140°/140°

3000K | >80 CRI | 2x480lm

CODE

720274D4



### ALWAYS USE

base with fixation plate

CODE

base 300	910013D0
base 400	910014D0
base 600	910016D0
base 800	910018D0
base 1000	910010D0

base with concrete fixation

CODE

base 300	910073D0
base 400	910074D0
base 600	910076D0
base 800	910078D0
base 1000	910070D0

### ALWAYS USE

base with fixation plate

CODE

base 300	910013D0
base 400	910014D0
base 600	910016D0
base 800	910018D0
base 1000	910010D0

base with concrete fixation

CODE

base 300	910073D0
base 400	910074D0
base 600	910076D0
base 800	910078D0
base 1000	910070D0