






# PYRAMID

CEILING RECESSED



## 1.0 LED111

LED 12W | 220-240VAC | 50-60Hz  
AC-COB 3-step | phase-cut dim  
aluminium powder coated

0.75kg IP20  $\pm 0.3 \pm D$   $\varnothing$   $\Delta$  38°  
196x196  $\angle$  35°/35°  $\uparrow$  355°  $\text{lm}$  100  $\text{lm}$  4-30

CODE
113368W_

### Light Colour Selection

LUMEN   CRI	CODE
2700K 680   >90	3
3000K 720   >90	5
1800-2850K 830   >80	9

## 1.0 LED111 HO

LED 15W | 220-240VAC | 50-60Hz  
AC-COB 3-step | phase-cut dim  
aluminium powder coated

0.75kg IP20  $\pm 0.3 \pm D$   $\varnothing$   $\Delta$  30°  
196x196  $\angle$  35°/35°  $\uparrow$  355°  $\text{lm}$  100  $\text{lm}$  4-30

CODE
113378W_

### Light Colour Selection

LUMEN   CRI	CODE
2700K 1050   >80	2
3000K 1200   >80	4

## 1.0 QR111

QR111 max.75W | G53  
12V | excl. power supply  
aluminium powder coated

0.51kg IP20  $\pm 0.9 \pm D$   
196x196  $\angle$  35°/35°  $\uparrow$  355°  $\text{lm}$  100  $\text{lm}$  4-30

CODE
113330W_

### ALWAYS USE

power supply	CODE
12V   10W dim	90221401
12V   25W dim	90221701
12V   70W dim	90221904

more specs on page 576