



HIDE

CEILING RECESSED



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.43kg IP20 0.3° 36°

45/45° 10° 125 4-25

CODE

	117161W
	117161S
	117161B

Light Colour Selection

	LUMEN	CRI	CODE
2700K	420-590	>90	3
3000K	470-640	>90	5
1800-2850K	370-510	>95	9

ALWAYS USE

power supply

CODE

350mA 10W	90213402
500mA 10W	90214403
500mA 15W dim	90224501

more power supplies on page 538

1.0 PAR16

PAR16 max.35W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.41kg IP20 0.9°

45/45° 13° 125 4-25

CODE

	117120W0
	117120S0
	117120B0

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

CODE

2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 541

ALWAYS USE

recessed housing + plaster kit

one lamp | 111x111x117mm

115x115 125 4-25

CODE

	90012009
	90012017

two lamps | 208x111x117mm

212x115 125 4-25

CODE

	90012010
	90012018

three lamps | 302x111x117mm

306x115 125 4-25

CODE

	90012011
	90012019


four lamps | 398x111x117mm

402x115 125 4-25

CODE

	90012012
	90012020

more information on page 549



back