



RAY

OUTDOOR WALL SURFACE



1.0


LED 6W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.47kg IP65

Color	CODE
White	741168W
Dark Grey	741168D
Black	741168B

Light Colour Selection

Color	LUMEN	CRI	CODE
2700K	400	>80	2
3000K	440	>80	4



2.0


2xLED 3W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.47kg IP65

Color	CODE
White	741148W
Dark Grey	741148D
Black	741148B

Light Colour Selection

Color	LUMEN	CRI	CODE
2700K	2x200	>80	2
3000K	2x220	>80	4



3.0


LED 6W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.53kg IP65

Color	CODE
White	741268W
Dark Grey	741268D
Black	741268B

Light Colour Selection

Color	LUMEN	CRI	CODE
2700K	400	>80	2
3000K	440	>80	4



4.0

2xLED 3W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.53kg IP65

Color	CODE
White	741248W
Dark Grey	741248D
Black	741248B

Light Colour Selection

Color	LUMEN	CRI	CODE
2700K	2x200	>80	2
3000K	2x220	>80	4