







BOX

OUTDOOR WALL SURFACE



p. 255 p. 327 p. 419 p. 451



1.0

LED 6W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.60kg IP65 $\beta=0,3^\circ$

	CODE
	740168W_
	740168D_
	740168B_

Light Colour Selection

	LUMEN	CRI	CODE
2700K	400	>80	2
3000K	440	>80	4

2.0

2xLED 3W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.66kg IP65 $\beta=0,3^\circ$

	CODE
	740148W_
	740148D_
	740148B_

Light Colour Selection

	LUMEN	CRI	CODE
2700K	2x200	>80	2
3000K	2x220	>80	4

3.0

LED 6W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.67kg IP65 $\beta=0,3^\circ$

	CODE
	740268W_
	740268D_
	740268B_

Light Colour Selection

	LUMEN	CRI	CODE
2700K	400	>80	2
3000K	440	>80	4

4.0

2xLED 3W | 220-240VAC | 50-60Hz
PCB 3-step | incl. PS | phase-cut dim
aluminium powder coated
incl. flaps for adjustable beam angle

0.86kg IP65 $\beta=0,3^\circ$

	CODE
	740248W_
	740248D_
	740248B_

Light Colour Selection

	LUMEN	CRI	CODE
2700K	2x200	>80	2
3000K	2x220	>80	4