


# DEEP ASYM

CEILING RECESSED



## 1.0 LED

LED 7/10W | 350-500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.25kg IP20  $\approx 0.3 \cdot D$   $\approx 36^\circ$

$\approx 87$   $\approx 35^\circ/35^\circ$   $\approx 355^\circ$   $\approx 100$   $\approx 4-30$

CODE
112461W_
112461S_
112461G_
112461B_

### Light Colour Selection

	LUMEN   CRI	CODE
2700K	420-590   >90	3
3000K	470-640   >90	5
1800-2850K	320-440   >95	9

## ALWAYS USE

power supply

	CODE
350mA   10W	90213402
500mA   10W	90214403
500mA   15W dim	90224501

more power supplies on page 538

## 1.0 MR16

QR-CBC51 max.35W | GU5.3  
12V | excl. power supply  
aluminium powder coated

0.19kg IP20  $\approx 0.9 \cdot D$

$\approx 87$   $\approx 35^\circ/35^\circ$   $\approx 355^\circ$   $\approx 90$   $\approx 4-30$

CODE
112410W0
112410S0
112410G0
112410B0

## ALWAYS USE

power supply

	CODE
12V   10W dim	90221401
12V   25W dim	90221701
12V   70W dim	90221904

more specs on page 540

## 1.0 PAR16

PAR16 max.35W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.23kg IP20  $\approx 0.9 \cdot D$

$\approx 87$   $\approx 35^\circ/35^\circ$   $\approx 355^\circ$   $\approx 115$   $\approx 4-30$

CODE
112420W0
112420S0
112420G0
112420B0

## OPTIONAL

PAR16 LED GU10 7W  
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 541