



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.16 kg \triangleleft IP44 S-0,3-1) C A-38°

76 S-60 S-4-30

CODE

154161W_
154161B_

1.0 MR16

QR-CBC51 max. 35W | GU5.3
12V | excl. power supply
aluminium powder coated

0.10 kg \triangleleft IP44 S-0,9-1) C

76 S-70 S-4-30

CODE

154110W0
154110B0

1.0 PAR16

PAR16 max. 35W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.14 kg \square IP44 S-0,9-1) C

76 S-95 S-4-30

CODE

154120W0
154120B0

Light Colour Selection

	LUMEN	CRI	CODE
2700K	420-590	>90	3
3000K	470-640	>90	5
1800-2850K	320-440	>95	9

ALWAYS USE

power supply

CODE

350mA 10W	90213402
500mA 10W	90214403
500mA 15W dim	90224501

more power supplies on page 538

ALWAYS USE

power supply

CODE

12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904

more specs on page 540

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

CODE

2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 541