




RAY

CEILING SUSPENDED



2.0 | 3.0 LED

LED 6W | 220-240VAC | 50-60Hz
COB 3-step | incl. PS | phase-cut dim
aluminium powder coated
brushed

0.62 | 0.76kg | IP20 | 0.3° | 36°

2.0

200mm

CODE

White	207764W
Grey	207764L
Black	207764P
Dark Grey	207764B

3.0

300mm

CODE


White	207864W
Grey	207864L
Black	207864P
Dark Grey	207864B

Light Colour Selection

	LUMEN	CRI	CODE
2700K	420	>90	3
3000K	440	>90	5
1800-2850K	360	>95	9



p. 271 p. 423 p. 455 p. 513



2.0 | 3.0 PAR16

PAR16 max. 35W | GU10
100-240VAC | 50-60Hz
aluminium powder coated
brushed

0.54 | 0.68kg | IP20 | 0.9°

2.0

200mm

CODE

White	207720W0
Grey	207720L0
Black	207720P0
Dark Grey	207720B0

3.0

300mm

CODE

White	207820W0
Grey	207820L0
Black	207820P0
Dark Grey	207820B0

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 577