




OBOQ ROUND

CEILING RECESSED



1.0 LED111

LED 10W | 220-240VAC | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium | steel powder coated

0.98kg IP20 3-0.3-D P A 38°

140 25°/25° 360° 150 2-25

CODE

	120168J_
	120168E_
	120168K_

Light Colour Selection

	LUMEN CRI	CODE
2700K	710 >80	2
3000K	730 >80	4

1.0 LED111 HO

LED 15W | 220-240VAC | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium | steel powder coated

0.98kg IP20 3-0.3-D P A 40°

140 25°/25° 360° 150 2-25

CODE

	120178J_
	120178E_
	120178K_

Light Colour Selection

	LUMEN CRI	CODE
2700K	1050 >80	2
3000K	1200 >80	4

1.0 QR11

QR11 max.75W | G53
12V | excl. power supply
aluminium | steel powder coated

0.70kg IP20 3-0.9-D

140 25°/25° 360° 150 2-25

CODE

	120130J0
	120130E0
	120130K0

ALWAYS USE

power supply

CODE

12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904

more specs on page 540

