






HIDE

CEILING RECESSED



1.0 LED111

LED 12W | 220-240VAC | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated

0.93kg IP20 3-0.3-1 38°

45°/45° 45°/45° 215 4-25

	CODE
	117268W
	117268S
	117268B

Light Colour Selection

	LUMEN	CRI	CODE
2700K	680	>90	3
3000K	720	>90	5
1800-2850K	830	>80	9

1.0 LED111 HO

LED 15W | 220-240VAC | 50-60Hz
AC-COB 3-step | phase-cut dim
aluminium powder coated

0.93kg IP20 3-0.3-1 30°

45°/45° 45°/45° 215 4-25

	CODE
	117278W
	117278S
	117278B

Light Colour Selection

	LUMEN	CRI	CODE
2700K	1050	>80	2
3000K	1200	>80	4

1.0 QR111

QR111 max.75W | G53
12V | excl. power supply
aluminium powder coated

0.73kg IP20 3-0.9-1

45°/45° 45°/45° 215 4-25

	CODE
	117230W0
	117230S0
	117230B0

ALWAYS USE

power supply

	CODE
12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904

more specs on page 576

ALWAYS USE

recessed housing + plaster kit

one lamp | 171x171x179mm

175x175 190 4-25

	CODE
	90012013
	90012021

two lamps | 327x171x179mm

331x175 190 4-25

	CODE
	90012014
	90012022

three lamps | 482x171x179mm

485x175 190 4-25

	CODE
	90012015
	90012023

four lamps | 638x171x179mm

640x175 190 4-25

	CODE
	90012016
	90012024

more information on page 585