



SNEAK TRIMLESS

CEILING RECESSED



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.19 kg IP20 \varnothing 0.3-1 \angle 32°

86x86 \angle 35°/35° \angle 355° \square 95 \square 9 or 12

CODE

155151W _
155151B _

Light Colour Selection

	LUMEN	CRI	CODE
2700K	335-470	>90	3
3000K	375-510	>90	5
1800-2850K	255-350	>95	9

2.0 LED

2xLED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.34 kg IP20 \varnothing 0.3-1 \angle 32°

86x156 \angle 35°/35° \angle 355° \square 95 \square 9 or 12

CODE

155251W _
155251B _

Light Colour Selection

	LUMEN	CRI	CODE
2700K	2x335-470	>90	3
3000K	2x375-510	>90	5
1800-2850K	2x255-350	>95	9

ALWAYS USE

plasterkit 90017116

power supply

CODE

350mA | 10W 90213402
500mA | 10W 90214403
500mA | 15W dim 90224501

more power supplies on page 538

ALWAYS USE

plasterkit 90017117

power supply

CODE

350mA | 10W 90213402
500mA | 10W 90214403
500mA | 15W dim 90224501

more power supplies on page 538