



### 1.0 LED

**LED** LED 7/10W | 350-500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.36kg IP20  $\approx 0.3 \cdot \text{D}$   $\text{P}$   $\text{A}$  36°

$\text{D}$  102  $\text{C}$  35°/35°  $\text{U}$  355°  $\text{I}$  90  $\text{E}$  4-40

	CODE
	111161W_
	111161S_
	111161B_

blade springs

	CODE
	111161W_C

### Light Colour Selection

	LUMEN	CRI	CODE
2700K	420-590	>90	3
3000K	470-640	>90	5
1800-2850K	320-440	>95	9

### ALWAYS USE

power supply

	CODE
350mA   10W	90213402
500mA   10W	90214403
500mA   15W dim	90224501

more power supplies on page 538

### 1.0 MR16

**QR-CBC51** max.35W | GU5.3  
12V | excl. power supply  
aluminium powder coated

0.30kg IP20  $\approx 0.9 \cdot \text{D}$

$\text{D}$  102  $\text{C}$  35°/35°  $\text{U}$  355°  $\text{I}$  75  $\text{E}$  4-40

	CODE
	111110W0
	111110S0
	111110B0

blade springs

	CODE
	111110W0C

### ALWAYS USE

power supply

	CODE
12V   10W dim	90221401
12V   25W dim	90221701
12V   70W dim	90221904

more specs on page 540

### 1.0 PAR16

**PAR16** max.35W | GU10  
100-240VAC | 50-60Hz  
aluminium powder coated

0.34kg IP20  $\approx 0.9 \cdot \text{D}$

$\text{D}$  102  $\text{C}$  35°/35°  $\text{U}$  355°  $\text{I}$  100  $\text{E}$  4-40

	CODE
	111120W0
	111120S0
	111120B0

blade springs

	CODE
	111120W0C

### OPTIONAL

PAR16 LED GU10 7W  
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 541